

High Wall Heat Pump Ductless System

Indoor Model: **DLFEHAH18XAK**


Submittal Data

Job Data: Location:

Buyer: Buyer P.O. #: Carrier #:

Unit Number: Model Number:

Performance Data Certified By: Date:



STANDARD FEATURES

- Up-Down Louver control (fixed or swing)
- Remove filter from the top
- Improved serviceability with easy access to fan and electrical connections
- Four fan speeds
- Sleep Mode
- Follow Me (senses temperature at handheld remote)
- Quiet operation
- Anti-corrosive fan coating

Controls:

- Wireless Remote Controller included with indoor unit
- Optional Wired Remote Controller KSACN0401AAA

System	Size	18	
	Indoor Model	DLFEHAH18XAK	
Electrical	Voltage, Phase, Cycle	V/Ph/Hz	208/230-1-60
	Power Supply	0	
	MCA	A.	0.28
Controls	Wireless Remote Controller (°F/°C Convertible)	Standard	
	Wired Remote Controller (°F/°C Convertible)	Optional	
Operating Range	Cooling Indoor DB Min -Max	° F (° C)	63~90 (17~32)
	Heating Indoor DB Min -Max	° F (° C)	32~86 (0~30)
Piping	Pipe Connection Size - Liquid	in (mm)	1/4 (6.35)
	Pipe Connection Size - Suction	in (mm)	1/2 (12.7)

Indoor Coil	Face Area (sq. ft.)	Sq. Ft.	2.58
	No. Rows	2	
	Fins per inch	20	
	Circuits	2	
Indoor	Unit Width	in (mm)	38.36 (974)
	Unit Height	in (mm)	12.8 (325)
	Unit Depth	in (mm)	8.87 (225)
	Net Weight	lbs (kg)	31.97(14.5)
	Number of Fan Speeds	4	
	Airflow (lowest to highest)	CFM	53/412/529/559
	Sound Pressure (lowest to highest)	dB(A)	34/39/44/46
	Air throw Data	ft (m)	25 (7.6)
Moisture removal	Pint/h (L/h)	4.63 (2.19)	
Field Drain Pipe Size O.D.	in (mm)	0.625 (16)	

Performance may vary based on the outdoor unit matched to. See compatible outdoor units pages for Performance Data.
For Compatibility See Product Data

Accessories

KSACN0401AAA	Wired Remote Control 7 day Programmable
KSAIF0601AAA	Wi-Fi™ Kit High Wall

Construction View

Indoor Model: DLFEHAH18XAK

