



About Duro Dyne

Products

New Products

Technical Support

Where to Buy

News and Events

Newsletter

Contact U

Adhesives

Air Regulation

DuroZone

Dyna-Tite

Dyn-O-Mate

Flexible Duct Connector

Insulation Fasteners

Machinery

Screws

Tools

Accessory

Files

Saws and Blades Hammers

Hole Cutter

HVAC Tools

Knives &
Blades
Metal Edge
Turners

Screwdrivers

Snips and Scissors Soldering Products Tapes and Rules Tube Cutter

Wire Stripper/Cutter Wrenches

Misc.

Espanol

Saws & Blades

General Purpose Hacksaw Frame

This is a sturdy, bright nickel frame with 3-1/2" throat. It can be adjusted for 10" or 12" blades in four positions. The blade holding bolt is equipped with a large wing nut tightener. It is assembled with a 10" Nicholson blade and can be adjusted 90 degrees for vertical or horizontal cuts.





Tool Product
Catalog >

No. 10 Hacksaw Frame

This hacksaw frame is corrosion proof, polished nickel with a 3-3/8" throat and is adjustable for 10" or 12" blades. The handle is molded plastic. The blade holding bolts are adjustable to four positions. The rear bolt has wing nut for easy tensioning of the blade. Each frame is assembled with a 10" Nicholson blade.



No. 12P High Tension Hacksaw Frame

This is a rugged, lightweight frame built for professional tool users. It lets you take full advantage of the high tensile strength of Nicholson® Bi-Metaloy® hand hacksaw blades but can be used with all other type blades, too. Use Nicholson® Bi-Metaloy® blades and achieve a remarkable improvement in cut-off performance – no blade twist, reduced binding, square cuts, better finish. Equipped with Bi-Metaloy® blades, this hacksaw cuts faster through the toughest materials, and the blades last longer. The secret is a screw-operated lever with a folding handle for tensioning the blade up to 30,000 psi. Ordinary frames may give you up to 15,000 psi maximum. The higher the tension setting, the greater the blade beam strength and cutting results. The frame is assembled with a 12" Blade.



Mini-Hacksaw

This is an ergonomic handle which gets into small places, making difficult cutting jobs easy. It uses a standard size hacksaw blade.



Bi-Metaloy® Hand Hacksaw Blades

Blades have a molybdenum alloy tool steel edge with a tough, flexible high carbon steel backing. They last twice as long as high speed steel and up to 10 times longer than carbon steel. They can be operated 20% to 50% faster. Additional features are high tooth hardness and shock resistance.



Reciprocating Saw Blades

Blades fit all reciprocating saws using a universal 1/2" shank. They are bi-metal construction for long life and rugged use. This alloy steel features excellent flexibility. The teeth are hardened, giving the blades a high-speed cutting edge, long life and durability. Thicker than most blades, teeth stay sharper longer, resisting over heating and embrittlement.



Productos en Español :: ©2010 Duro Dyne Corporation :: sitemap