



13SEER&14SEER Rooftop Package Units



13/14SEER R410A
Horizontal / Downflow Discharged



13SEER R410A
Horizontal Discharged

Features

- Wide-capacity range in both cooling only and heat pump models.
- High-efficiency 13 and 14 SEER ratings.
- Architecturally compatible, anti-rust steel cabinets. 1,000-hour salt spray tested.
- Removable bottom for side- or bottom return applications.
- High-efficiency compressors operate smoothly, quietly, consistently.
- Internal safeguards protect compressor against high pressure, low pressure, coil temperature and power surge.(heat pump only).
- Reliable thermostatic operation, with either Midea or many other brand-name controller..
- Auxiliary electric heaters (5kW,7.5kW, 10kW, 15kW, 20kW, 25kW) .

AHRI Certified and ETL Listed.



Single Phase 14SEER Horizontal/Downflow Discharged

MAMRB30H14

Sale Model			208/230-1Ph-60Hz
Power supply	V-Ph-Hz		208/230-1Ph-60Hz
Cooling	Capacity	Btu/h	28600
	SEER		14
Heating	Capacity	Btu/h	28800
	HSPF		8
MCA	A		20.8
MOP	A		30
Compressor	Type		Scroll
	Rated current(RLA)	A	14.1
	Locked rotor Amp(LRA)	A	73
Indoor fan motor	Model		YDK195-6E
	Type		PSC
	Output	HP	1/3
	Capacitor	uF	10
	RPM		1075
Side supply /Side return duct dimensions(W*D)	inch		14-1/2x14-1/2
Bottom supply /Bottom return duct dimensions(W*D)	inch		15x15
Outdoor fan motor	Model		YDK110-8G-1
	Type		PSC
	Output	HP	1/6
	Capacitor	uF	6
	RPM		825
Outdoor sound level(sound pressure level)	dB(A)		60
Outdoor unit	Dimension(WXHXD)	mm	1920x714x1068
	Packing(WXHXD)	inch	75-5/8x28-1/8x42
	Net/Gross weight	Lbs.	441/450
Shipping (40HQ)			36

Sale Model			MRB-36CWN1-M14	MRB-36HWN1-M14	MRB-42CWN1-M14	MRB-42HWN1-M14
Power supply	V-Ph-Hz		208/230-1Ph-60Hz	208/230-1Ph-60Hz	208/230-1Ph-60Hz	208/230-1Ph-60Hz
Cooling	Capacity	Btu/h	35800	36000	42000	42000
	SEER		14	14	14	14
Heating	Capacity	Btu/h	/	36000	/	42000
	HSPF		/	8	/	8
MCA	A		24.5	24.5	27	27.7
MOP	A		40	40	40	40
Compressor	Type		Scroll	Scroll	Scroll	Scroll
	Rated current(RLA)	A	16.7	16.7	17.9	17.9
	Locked rotor Amp(LRA)	A	79	79	112	112
Indoor fan motor	Model		YDK270-6E	YDK270-6E	YDK450-6E	YDK450-6E
	Type		PSC	PSC	PSC	PSC
	Output	HP	1/2	1/2	3/4	3/4
	Capacitor	uF	10	10	15	15
	RPM		1075	1075	1075	1075
Side supply /Side return duct dimensions(W*D)	inch		14-1/2x14-1/2	14-1/2x14-1/2	14-1/2x14-1/2	14-1/2x14-1/2
Bottom supply /Bottom return duct dimensions(W*D)	inch		15x15	15x15	15x15	15x15
Outdoor fan motor	Model		YDK110-8G-1	YDK110-8G-1	YDK110-8G-1	YDK230-6G-1
	Type		PSC	PSC	PSC	PSC
	Output	HP	1/6	1/6	1/6	1/3
	Capacitor	uF	6	6	6	15
	RPM		825	825	825	1075
Outdoor sound level(sound pressure level)	dB(A)		58	57	60	62
Outdoor unit	Dimension(WXHXD)	mm	1920x714x1068	1920x714x1068	1920x840x1068	1920x840x1068
	Packing(WXHXD)	inch	75-5/8x28-1/8x42	75-5/8x28-1/8x42	75-5/8x33x42	75-5/8x33x42
	Net/Gross weight	Lbs.	423/441	441/450	469/505	505/514
Shipping (40HQ)			36	36	36	36

Ultimate data changing right reserved by manufacturer.

Three Phase 14SEER Horizontal/Downflow Discharged

Sale Model			MRB-36CWN1-X14	MRB-36HWN1-X14B	MRB-48CWN1-X14	MRB-48HWN1-X14	MRB-60CWN1-X14B	MRB-60HWN1-X14B
Power supply		V-Ph-Hz	208/230-3Ph-60Hz	208/230-3Ph-60Hz	208/230-3Ph-60Hz	208/230-3Ph-60Hz	208/230-3Ph-60Hz	208/230-3Ph-60Hz
Cooling	Capacity	Btu/h	36000	35200	48000	47800	59500	58500
	SEER		14	14	14	14	14	14
Heating	Capacity	Btu/h	/	36000	/	48000	/	59000
	HSPF		/	8	/	8	/	8
MCA		A	16.6	16.6	22.5	22.5	27.3	27.3
MOP		A	25	25	35	35	40	40
Compressor	Type		Scroll	Scroll	Scroll	Scroll	Scroll	Scroll
	Rated current(RLA)	A	10.4	10.4	13.7	13.7	16	16
	Locked rotor Amp(LRA)	A	73	73	83.1	83.1	110	110
Indoor fan motor	Model		YDK270-6E	YDK270-6E	YDK400-6E	YDK400-6E	ECM-140-735-2000	ECM-140-735-2000
	Type		PSC	PSC	PSC	PSC	ECM	ECM
	Output	HP	1/2	1/2	3/4	3/4	1	1
	Capacitor	uF	10	10	20	20	/	/
	RPM		1075	1075	1075	1075	/	/
Side supply /Side return duct dimensions(W*D)		inch	14-1/2x14-1/2	14-1/2x14-1/2	14-1/2x14-1/2	14-1/2x14-1/2	14-1/2x14-1/2	14-1/2x14-1/2
Bottom supply /Bottom return duct dimensions(W*D)		inch	15x15	15x15	15x15	15x15	15x15	15x15
Outdoor fan motor	Model		YDK110-8G-1	YDK110-8G-1	YDK230-6G-1	YDK230-6G-1	YDK230-6G-1	YDK230-6G-1
	Type		PSC	PSC	PSC	PSC	PSC	PSC
	Output	HP	1/6	1/6	1/3	1/3	1/3	1/3
	Capacitor	uF	6	6	15	15	15	15
	RPM		825	825	1075	1075	1075	1075
Outdoor sound level(sound pressure level)		dB(A)	61	60	62	62	63	65
Outdoor unit	Dimension(WXHXD)	mm	1920×714×1068	1920×714×1068	1920×840×1068	1920×840×1068	1920×840×1068	1920×840×1068
	Packing(WXHXD)	inch	75-5/8×28-1/8×42	75-5/8×28-1/8×42	75-5/8×33×42	75-5/8×33×42	75-5/8×33×42	75-5/8×33×42
	Net/Gross weight	Lbs.	432/441	441/450	496/505	505/514	507/516	516/525
Shipping (40HQ)			36	36	36	36	36	36

Ultimate data changing right reserved by manufacturer.



GD Midea Heating & Ventilating Equipment Co., Ltd.
Is certified under the ISO 9001 International standard
for quality assurance.
NO.01 100 019209



GD Midea Heating & Ventilating Equipment Co., Ltd.
Is certified under the ISO 14001 International standard
for environmental management.
Certificate No. 15912E10020R0L

Dealer information

Commercial Air Conditioner Business Units

Midea Group

Add: West region of Midea commercial air conditioner department, Industry Avenue,
Beijiao, Shunde, Foshan, Guangdong, P.R. China Postal code: 528311

Tel: +86-757-22390820 Fax: +86-757-23270470

<http://global.midea.com.cn>

<http://www.midea.com>

Note: The data in this book may be changed without notice for further improvement
on quality and performance.