



# Commercial Air Handler

Match with cooling only  
or heat pump operation

Suitable for use with  
R410A and R22  
refrigerants

Multi-speed PSC motor



Electric heater:  
5kW/7.5W/10kW



**AHRI CERTIFIED**<sup>®</sup>  
[www.ahridirectory.org](http://www.ahridirectory.org)

VAV Terminals  
AHRI Standard 880



# Specifications - R410A Wall mounted

Sale Model			MVB-24WN1-M13
Power supply		V-Ph-Hz	208/230V 1Ph 60Hz
MCA		AMPS	1.3
MOP		AMPS	15
MOTOR	Model		YDK165-6Q
	Type		PSC
	Capacitor	uF	6
	Rated HP		0.25
	Rated RPM	r/min	1075
Indoor fan	material		Metal
	Type		Fan impeller
	Diameter	inch	10-3/4
	Height	inch	6
In door coil type			Copper tube and Alumin
Indoor limitvalue of static pressure and air flow		Pa/CFM	25/850
Indoor sound level (sound pressure level)		dB(A)	54
Indoor unit	Dimension (W*H*D)	inch	20-1/2x36 -1/2x15
	Packing (W*H*D)	inch	23-1/5x40 -1/4x18 -1/2
	Net/Gross weight	lbs	88/99
throttle type			Orifice
Refrigerant connection valve size	Liquid side/ Gas side	inch	3/8 / 3/4
Shipping per STD40HQ			258

Ultimate data changing right reserved by manufacturer.