



Commercial Air Handler

Match with cooling only
or heat pump operation

Suitable for use with
R410A and R22
refrigerants

Multi-speed PSC motor



Electric heater:
5kW/7.5W/10kW



VAV Terminals
AHRI Standard 880

Specifications - R410A Wall mounted

Sale Model			MVB-36WN1-M13
Power supply		V-Ph-Hz	208/230V 1Ph 60Hz
MCA		AMPS	2.3
MOP		AMPS	15
MOTOR	Model		YDK270-6F
	Type		PSC
	Capacitor	uF	10
	Rated HP		0.5
	Rated RPM	r/min	1075
Indoor fan	material		Metal
	Type		Fan impeller
	Diameter	inch	10-3/4
	Height	inch	8
In door coil type Copper tube and Aluminum fin			
Indoor limitvalue of static pressure and air flow		Pa/CFM	25/1213
Indoor sound level (sound pressure level)		dB(A)	54
Indoor unit	Dimension(W*H*D)	inch	22x39-1/2x19
	Packing (W*H*D)	inch	224-4/5x42-1/3x21-4/5
	Net/Gross weight	lbs	110/121
throttle type			Orifice
Refrigerant connection valve size	Liquid side/ Gas side	inch	3/8 / 3/4
Shipping per STD40HQ			176

Ultimate data changing right reserved by manufacturer.