

Model			MTB1-30WN1-M14	
Electrical	Power supply	V-Ph-Hz	208/230V-1Ph-60Hz	
	Minimum Circuit Ampacity	A	2.2	
	Max. Overcurrent Protection	A	15	
Indoor motor	Type		PSC	
	Capacitor	uF	10	
	Rated RPM	RPM	1600	
	Rated HP	HP	1/3	
	FLA	A	1.8	
Indoor fan	material		galvanized sheets	
	Type		centrifugal fan	
	Diameter	in.	7	
	Height	in.	9	
Indoor coil	Fin type		hydrophilic aluminum	
	Tube outside dia.and type	in.	9/32" Inner groove copper tube	
	Rows-F.P.I		3-17	
Indoor External Static Pressure <sup>1</sup>		In w.g.(Pa)	37.5	
Indoor Air Flow <sup>2</sup>		CFM	1000	
Indoor sound pressure level		dB(A)	62.5	
System	Refrigeration control		TXV	
	Liquid side/ Suction side	in.	3/8 3/4	
Indoor unit	Dimension (W*H*D)	mm	1315×280×704	
		in.	51-3/4×11×27-3/4	
	Packing (W*H*D)	mm	1450×350×785	
		in.	57×13-3/4×31	
	Net/Gross weight	kg	60/69	
		lbs	132/152	
Drain Conn.Size		in.	3/4" NPT	
Shipping per STD40HQ			154	

Notes

1,2:See more data from the installation instructions

3:See the specification manual for rating data and required orifice or TXV model