

| | | | | |
|--|-----------------------------|-------------|--------------------------------|--|
| Model | | | MTB2-36WN1-M15 | |
| Electrical | Power supply | V-Ph-Hz | 208/230V-1Ph-60Hz | |
| | Minimum Circuit Ampacity | A | 15 | |
| | Max. Overcurrent Protection | A | 35 | |
| | Type | | ECM | |
| | Capacitor | uF | / | |
| | Rated RPM | RPM | 1050 | |
| | Rated HP | HP | 1/3 | |
| | FLA | A | 2.6 | |
| Indoor fan | material | | galvanized sheets | |
| | Type | | centrifugal fan | |
| | Diameter | in. | 7 | |
| | Height | in. | 9 | |
| Indoor coil | Fin type | | hydrophilic aluminum | |
| | Tube outside dia.and type | in. | 9/32" Inner groove copper tube | |
| | Rows-F.P.I | | 3-17 | |
| Indoor External Static Pressure ¹ | | In w.g.(Pa) | 37.5 | |
| Indoor Air Flow ² | | CFM | 1200 | |
| Indoor sound pressure level | | dB(A) | 62.5 | |
| System | Refrigeration control | | TXV | |
| | Liquid side/ Suction side | in. | 3/8 3/4 | |
| Indoor unit | Dimension (W*H*D) | mm | 1315×280×704 | |
| | | in. | 51-3/4×11×27-3/4 | |
| | Packing (W*H*D) | mm | 1450×350×785 | |
| | | in. | 57×13-3/4×31 | |
| | Net/Gross weight | kg | 62/69 | |
| lbs | | 137/152 | | |
| Drain Conn.Size | | in. | 3/4" NPT | |
| Shipping per STD40HQ | | | 154 | |

Notes

1,2:See more data from the installation instructions

3:See the specification manual for rating data and required orifice or TXV model