

## Bully Hog Blades – The Toughest Blades made!

### Features:

- Bi-metal
- Matrix II high speed steel & 8% cobalt edge
- Tooth hardness Rc 65-66

### Advantages:

- Shatter & shock resistant teeth
- High heat and extra wear resistant
- High edge hardness for aggressive cutting
- Cuts faster through the toughest materials & lasts longer with sharp teeth

<b>BULLY HOG™ RECIPROCATING BLADE</b>					
5 Per Vinyl Pouch	Bulk Packed 25 Per Box	Length x Width x Thickness		Teeth Per Inch/ 25 mm	Shape
		Inches	Millimeters		
ST-42	ST-42-1	6x3/4x.035	150x20x.9	6	
Recommended Use: Fast Cutting for non-ferrous metals, plastics, wood and composition materials					
ST-43	ST-43-1	6x3/4x.050	150x20x1.3	6	
ST-44	ST-44-1	9x3/4x.050	225x20x1.3	6	
ST-45	ST-45-1	12x3/4x.050	300x20x1.3	6	
Recommended Use: Roughing-In work. Nail embedded wood					
ST-103	ST-103-1	6x3/4x.035	150x20x.9	10	
ST-104	ST-104-1	8x3/4x.035	200x20x.9	10	
Recommended Use: Nail embedded wood, non-ferrous metals					
ST-98	ST-98-1	8x3/4x.035	200x20x.9	10/14	
ST-97	ST-97-1	8x3/4x.050	200x20x1.3	10/14	
ST-96	ST-96-1	12x3/4x.050	300x20x1.3	10/14	
Variable Pitch Recommended Use: General Purpose wood and metals					
ST-46	ST-46-1	4x3/4x.035	100x20x.9	14	
ST-47	ST-47-1	6x3/4x.035	150x20x.9	14	
ST-99	ST-99-1	8x3/4x.035	200x20x.9	14	
ST-48	ST-48-1	12x3/4x.050	300x20x1.3	14	
Recommended Use: Cuts heavy gauge metal, bar stock, angle iron, fiber and hard rubber					
ST-49	ST-49-1	4x3/4x.035	100x20x.9	18	
ST-50	ST-50-1	6x3/4x.035	150x20x.9	18	
ST-100	ST-100-1	8x3/4x.035	200x20x.9	18	
Recommended Use: Cuts structural steel, stainless steel, pipe and metal conduit.					
ST-51	ST-51-1	4x3/4x.035	100x20x.9	24	
ST-52	ST-52-1	6x3/4x.035	150x20x.9	24	
Recommended Use: Cuts all metal, trim and tubing under 1/8" thickness. Cuts galvanized pipe 18 gauge and under.					

## RECIPROCATING BLADE CROSS REFERENCE

Product Number	Lenox	Malco	Milwaukee	Bosch	Morse
ST-42	606R	-	-	S811DF	-
ST-43	656R	4KH8/4KH6	48-01-5031	S611DF	RB65006B
ST-44	956R	8KH7	48-01-5036	S1544DF	RB95006B
ST-45	156R	12KH8	48-01-5037	S1344DF	RB125006B
ST-46	414R	-	48-01-5181	S518B	RB414B
ST-47	614R	4TF14	48-01-5182	S918B	RB614B
ST-48	-	-	-	S1211H	-
ST-49	418R	3TF18	48-01-5183	S518E	RB418B
ST-50	618R	4TF18	48-01-5184	S918E	RB618B
ST-51	424R	3MC24	48-01-5185	S518EF	RB424B
ST-52	624R	4MC24	48-01-5186	S918A	RB624B
ST-96	110R	-	-	S1222VF	-
ST-97	-	9MC10	48-01-3093	S1122VF	RB8501014B
ST-98	-	-	48-01-5193	-	RB81014B
ST-99	-	-	48-01-5187	S118BF	-
ST-100	818R	-	48-01-5188	S1122EF	RB918B
ST-101	600RG	-	48-02-1420	-	RTC66
ST-102	800RG	8CG	48-02-1430	S113ORF2	RTC68
ST-103	610R	4GT10	48-01-5092	S811HF	RB610B
ST-104	810R	9ML10	48-01-5093	S1018H	RB810B
ST-120	966R	-	48-00-5026	S610DF	RB96206B
ST-128	960R	-	48-00-5026	S1120CF	RB96210B