# **MVME** Series **Multi-position Air handler** 1.5-5 Ton

#### **Standard Features**

- \* Available for cooling and heat pump applications.
- Multi-speed ECM blower motor.
- All-aluminum tubes & fins.
- Common Factory-sealed cabinet certified to achieve 2% or less leakage rate at 1.0 inch water column.
- Multi-position Installation.
- \* Horizontal and vertical condensate drain pans standard;
- \* Blower and coil easy slide out for ease of maintenance.
- Field Installed heater kits are optional: 5/7.5/10/15/20kW.
- \* AHRI Listed & ETL Certified.

#### **Midea Building Technologies Division**

Add.: Midea Headquarters Building, 6 Midea Avenue, Shunde, Foshan, Guangdong, China

Postal code: 528311

mbt.midea.com / global.midea.com / tsp.midea.com

Note: Product specifications change from time to time as product improvements and developments are released and may vary from those in this document.



## Midea-Discover Easy Comfort

# Midea










### **Specifications**

| Model                            | MVMP18A1MN1OC | MVMP24B1MN1OC | MVMP36B1MN1OC | MVMP48C1MN1OC | MVMP60C1MN10C |
|----------------------------------|---------------|---------------|---------------|---------------|---------------|
| NOMINAL CAPACITY                 |               |               |               |               |               |
| Cooling (BTU/h)                  | 18,000        | 24,000        | 36,000        | 48,000        | 60,000        |
| External Static Pressure(in.w.c) | 0.6           | 0.6           | 0.6           | 0.7           | 0.8           |
| ELECTRICAL DATA                  |               |               |               |               |               |
| Voltage / Phase (60 Hz)          | 208/230/1     | 208/230/1     | 208/230/1     | 208/230/1     | 208/230/1     |
| Min. / Max. Voltage              | 187/253       | 187/253       | 187/253       | 187/253       | 187/253       |
| Min. Circuit Amps                | 1.9           | 2.9           | 3.3           | 4.2           | 5.7           |
| Max. Overcurrent Protection      | 15            | 15            | 15            | 15            | 15            |
| FAN MOTOR                        |               |               |               |               |               |
| Motor Type                       | PSC           | PSC           | PSC           | PSC           | PSC           |
| Capacitor (uF)                   | 6             | 10            | 10            | 20            | 20            |
| Horsepower (HP)                  | 1/5           | 1/4           | 1/2           | 1/2           | 3/4           |
| Rated RPM                        | 755           | 903           | 865           | 925           | 990           |
| Full Load Amps (FLA)             | 1.5           | 2.3           | 2.6           | 3.3           | 4.5           |
| FAN BLOWER                       |               |               |               |               |               |
| Material                         | Metal         | Metal         | Metal         | Metal         | Metal         |
| Туре                             | Centrifugal   | Centrifugal   | Centrifugal   | Centrifugal   | Centrifugal   |
| Diameter(in.)                    | 10-5/8        | 13            | 13            | 13            | 13            |
| Height(in.)                      | 10-3/4        | 10-5/8        | 10-5/8        | 10-5/8        | 10-5/8        |
| EVAPORATOR COIL                  |               |               |               |               |               |
| Туре                             | Tube & Fin    |
| Tube Material                    | Aluminum      | Aluminum      | Aluminum      | Aluminum      | Aluminum      |
| Tube Size(in.)                   | 9/32          | 9/32          | 9/32          | 9/32          | 9/32          |
| REFRIGERANT CONNECTION SIZE      |               |               |               |               |               |
| Liquid Line Size (O.D.)          | 3/8           | 3/8           | 3/8           | 3/8           | 3/8           |
| Suction Line Size (O.D.)         | 3/4           | 3/4           | 3/4           | 7/8           | 7/8           |

#### **Dimensions**



| Model                      | MVMP18A1MN1OC | MVMP24B1MN1OC | MVMP36B1MN1OC | MVMP48C1MN1OC | MVMP60C1MN10C |
|----------------------------|---------------|---------------|---------------|---------------|---------------|
| UNIT DIMENSION AND WEIGHTS |               |               |               |               |               |
| Height(in.)                | 41-3/8        | 46-1/2        | 46-1/2        | 54-1/2        | 54-1/2        |
| Width(in.)                 | 18-1/8        | 19-5/8        | 19-5/8        | 22            | 22            |
| Depth(in.)                 | 20-1/2        | 21-5/8        | 21-5/8        | 24            | 24            |
| Weight(lbs.)               | 108           | 128           | 128           | 159           | 161           |

UPFLOW UNIT SHOWN; UNIT MAY BE INSTALLED UPFLOW, DOWNFLOW, HORIZONTAL RIGHT OR LEFT AIR SUPPLY.

— 3 —