

Berry 555 FLEXFIX UL 181B-FX LISTED Film Tape - 555 FlexFix

Product Information Sheet

SKU/Product ID/Reference

555 FlexFix

Product Description

UL 181B-FX LISTED Film Tape for HVAC



Features and Benefits

- OPP Backing
 - Tough and durable
 - Hand tearable for ease of use
 - High visibility print (red on metallic, white on black) for easy inspection
- Acrylic Adhesive
 - Solvent-free, low odor
 - Aggressive, high tack bond
 - Mold and moisture resistant
- UL 181B-FX Listed
 - Meets code requirements and can contribute toward requirements for EA Credit 1 (Optimize Energy Performance) under LEED®
- Low VOC Content
 - Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

Regions Available

Global

Product Information

Adhesive Type	Acrylic
Carrier / Support / Facestock	BOPP Film
Gauge / Mil	3.1 mil
OEM / Specification Body & Specification	UL > 181B-FX Listed
Operating Temp Range	-40 to 212 °F
Peel Strength / Adhesion to Backing (oz/in)	35 oz/in
Peel Strength / Adhesion to Steel	45 oz/in
Tensile Strength	34 lb/in
VOC Content	0 g/L
Color(s)	Black Custom Color
Custom color(s)	Metallic
Product Construction	Single-Coated Tape

berryglobal.com

Specifications are subject to change without notice.